



Sialex®Ring Spezifikationen

| Größe | | max. Wasserdurchfluß (m ³ /h) | | | A (in mm) | B (in mm) | C (in mm) | t (in mm) |
|--------|-----|------------------------------------------|-----------|---------|-----------|-----------|-----------|-----------|
| Zoll | DN | Classic | Industrie | Optimum | | | | |
| 1/2" | 15 | 1,0 | 4,0 | 40,0* | 24,0 | 76,0 | 25,0 | 30,0 |
| 3/4" | 20 | 1,0 | 4,0 | 40,0* | 31,0 | 83,0 | 25,0 | 30,0 |
| 1" | 25 | 1,0 | 4,0 | 40,0* | 37,0 | 89,0 | 25,0 | 30,0 |
| 1 1/4" | 32 | 1,0 | 4,0 | 40,0* | 46,0 | 98,0 | 25,0 | 30,0 |
| 1 1/2" | 40 | 1,5 | 8,0 | 60,0* | 51,0 | 103,0 | 25,0 | 30,0 |
| 2" | 50 | 1,5 | 8,0 | 60,0* | 63,0 | 125,0 | 30,0 | 30,0 |
| 2 1/2" | 65 | XXX | 16,0 | 80,0* | 75,0 | 137,0 | 30,0 | 30,0 |
| 3" | 80 | XXX | 16,0 | 110,0* | 91,0 | 153,0 | 30,0 | 40,0 |
| 4" | 100 | XXX | 30,0* | 250,0* | 120,0 | 192,0 | 35,0 | 40,0 |
| 5" | 125 | XXX | 30,0* | 400,0* | 150,0 | 222,0 | 35,0 | 40,0 |
| 6" | 150 | XXX | 60,0* | 550,0* | 180,0 | 252,0 | 35,0 | 40,0 |
| 8" | 200 | XXX | 60,0* | 650,0* | 230,0 | 312,0 | 40,0 | 40,0 |
| 10" | 250 | XXX | 80,0* | 800,0* | 285,0 | 367,0 | 40,0 | 60,0 |
| 12" | 300 | XXX | 80,0* | 1000,0* | 335,0 | 417,0 | 40,0 | 60,0 |